


SMART CONTROLLER

CA MANAGEMENT INTEGRATED INTO CO₂ ABSORBER

- Integration into the CO₂ absorber
- Programming gas rate control setpoints
- Automatic regulation by conditioned release
- Smart CA management

The system measures and makes corrections to reach the configured setpoints.



Number of CA Cold rooms : 1 - 10 (1 Smart Controller per absorber)

Smart Controller Management tool

- Display: 5.7-inch colour touchscreen
- Remote access to the screen via Microsoft Internet Explorer and mobile application
- Connection: Ethernet network
- Memory: USB
- Automatic e-mailing system
- Sequential temperature measurement system
- Network printer link (HP PCL4 type)



Available languages: English / French / Spanish / Portuguese

TECHNICAL DATA

VALUE	SENSOR	SCALE	ACCURACY	TYPE OF MANAGEMENT
O ₂	Zirconium dioxide cell	0-25 %	+/- 0.1 %	Proportional
CO ₂	NDIR	0-5 % 0-10 % 0-30 % 0-100 %	+/- 0.1 %	Proportional
C ₂ H ₄	X	X	X	X
Temperature	PT100	-10 +40 °C (other on demand)	+/- 0.1 °C	∅
Pressure	Additional Controller	-50 + 50 mmH ₂ O	+/- 0.1 mmH ₂ O	Real Time
Humidity	X	X	X	X
Data Storage	USB pen drive	Connection	6/8 (prelevement)	
Remote access	Optional	Analysis flowrate	1 l/m	
Power supply	Three-phase 400 V / 50 Hz	Distance prelevement	Up to 200m	

OPTIONS